

the leader in marine propulsion.

And we do it all for you.

SO YOU CAN GO FASTER. GO FARTHER.









VERADO®

Our premium outboard platform redefines the category with advanced engineering, innovative technology and refined operation.

250 - 350 HP





FOURSTROKE

Backed by decades of experience on water all over the world, our FourStroke models deliver reliable, economical performance you can count on season after season.

2.5 - 300 HP

16





PRO XS®

Outboards with the hard-charging performance to put you out front and keep you there, Pro XS is the choice of tournament anglers and performance enthusiasts.

115 - 300 HP





SEAPRO™

Hard-working partners for people who make their living on the water, Mercury SeaPro outboards are engineered to meet the demands of commercial use.

15 - 300 HP

4







Mercury Verado® engines represent the pinnacle of superior outboard design and performance. Built to power the largest boats for the boldest adventures, Verado engines boast advanced engineering and refined operation for boat owners who refuse to compromise. Every Verado feature is designed to deliver the ultimate, most satisfying on-water experience.







EXHILARATING PERFORMANCE

No outboard in the class offers more displacement than the Verado V-8 4.6-liter. The performance-inspired 32-valve double-overhead-cam (DOHC) design and long, tuned intake runners produce more torque and allow the engine to reach higher engine speeds (rpm) faster. Weight is trimmed to 600 pounds for improved power-to-weight. Transient Spark calibration optimizes spark timing to boost hole-shot torque by as much as 7 percent, so you can get on plane and get going in an instant.

SUPERIOR FUEL ECONOMY

V-8 Verado outboards deliver superior fuel economy at cruising speed and wide-open throttle. Advanced Range Optimization (ARO) calibration precisely adjusts the fuel mixture and delivers the best possible efficiency at any speed. Verado V-8 outboards are calibrated to deliver full performance on 87-octane fuel.

SMOOTH AND QUIET

250hp and 300hp Verado deliver class-leading smooth and quiet performance. The next-generation Advanced MidSection (AMS) on moves engine mounts aft and outward to virtually eliminate vibration. Engine noise is minimized by a tuned multi-chamber air intake, fuel-injector covers that decrease high-frequency noise, and a highly engineered cowl sealing system.





EFFORTLESS OPERATION

Verado comes standard with SmartCraft® Digital Throttle & Shift (DTS) for ultrasmooth shifting, instantaneous throttle response, as well as electro-hydraulic, automotive-style power steering that provides precision handling.

ADVANCED SOUND CONTROL

You can customize the exhaust tone of a V-8 Verado outboard with industryexclusive Advanced Sound Control. The dual muffler system allows you to toggle between an ultra-quiet mode and a deeper, sportier tone.

ADAPTIVE SPEED CONTROL

Whether you're heading up a swell or into a tight turn, Adaptive Speed Control on V-8 Verado outboards automatically maintains the set rpm even as load or conditions change. That means you make far fewer throttle adjustments.

EXTRA CHARGING POWER

A class-leading 115-amp alternator helps V-8 Verado outboards keep batteries charged and ready on boats rigged with power-draining accessories. The Idle Charge battery-management system automatically increases idle rpm to boost alternator output and recharge low batteries to the proper level.

JOYSTICK PILOTING FOR OUTBOARDS

Mercury Verado outboards on multi-engine rigs equipped with Joystick Piloting for Outboards offer fingertip control of throttle, shift and steering, so you can dock precisely, safely and with confidence. Move sideways, diagonally or spin the boat on its own axis with total control in wind or current.





COLOR CHOICES

Three shades of white - Cold Fusion White, Warm Fusion White and Pearl Fusion White - and traditional Phantom Black are available on Mercury Verado outboards.





Phantom Black





Pearl Fusion White





Warm Fusion White





Cold Fusion White



ACCENT PANEL COLORS

For ultimate personalization of 250 and 300hp Verado outboards, four colors of factory-painted accent panels are available as kits. The panels are made from thin and durable polycarbonate that adhere firmly and provide color harmonization with a wide variety of boat colors.













350 verado

| Horsepower | 350 |
|--------------|---|
| WOT RPM | 5800-6400 |
| Engine Type | Inline-6 |
| Displacement | 158.5 cu in (2.6L) |
| Induction | Supercharged w/charge air cooling, 24-valve, DOHC |
| Starting | SmartStart electric |
| Gear Ratio | 5.44 in (1.75:1) HD |
| Alternator | 70 amp (882 watt) |
| Trim System | Power trim and tilt |
| Dry Weight* | 668lbs (303kg) |
| Steering | Electro-hydraulic power steering; JPO (optional) |
| Shaft Length | 20in (508mm) 25in (635mm) 30in (762mm) |



250/300 verado

| Horsepower | 250 | 300 |
|--------------|--|--|
| WOT RPM | 5200-6000 | 5200-6000 |
| Engine Type | V-8 | V-8 |
| Displacement | 279 cu in (4.6L) | 279 cu in (4.6L) |
| Induction | 32-valve DOHC | 32-valve DOHC |
| Starting | SmartStart electric | SmartStart electric |
| Gear Ratio | 1.85:1 | 1.85:1 or 1.75:1 |
| Alternator | 115 amp (1449 watt) | 115 amp (1449 watt) |
| Trim System | Power trim and tilt | Power trim and tilt |
| Dry Weight* | 600lbs (272kg) | 600lbs (272kg) |
| Steering | Electro-hydraulic power steering; JPO (optional) | Electro-hydraulic power steering; JPO (optional) |
| Shaft Length | 20in (508mm) 25in (635mm) 30in (762mm) | 20in (508mm) 25in (635mm) 30in (762mm) |



Active Trim

Active Trim makes boating easier and more enjoyable by automatically trimming outboard and sterndrive engines. Active Trim simplifies boat operation while improving engine performance and decreasing fuel costs.

Active Trim is compatible with all current SmartCraft-capable Mercury outboards (40hp and above).



VesselView Mobile TM

VesselView Mobile allows boaters to use a mobile device (smartphone or tablet) to connect with their Mercury outboard or sterndrive engine(s). The plug-and-play module connects to your device via Bluetooth, providing quick, convenient access to your engine's data.

VesselView Mobile is compatible with all SmartCraft-capable Mercury outboards (2004 and newer, 40hp and above).





Factory-backed

Every Mercury Verado comes with class-leading corrosion protection and an industry-exclusive three-year limited corrosion warranty.

Digital Throttle & Shift

Verado comes standard with SmartCraft Digital Throttle & Shift (DTS) for ultra-smooth shifting, instantaneous throttle response, as well as electro-hydraulic, automotive-style power steering that provides precision handling.

Standard on 250, 300 and 350hp Verado outboards.



Joystick Piloting

Joystick Piloting for Outboards - designed for dual, triple and quad Verado-powered vessels and personalized for each boat model - was the industry's first joystick system for outboards, and it remains the best-selling marine joystick system.

Optional on 250, 300 and 350hp Verado outboards.







Mercury's mid-range and smaller FourStroke outboards are engineered to deliver amazing performance in a package that's light and efficient. With innovative designs and advanced technology, these compact and versatile Mercury outboards are quiet, responsive and reliable in the shallows and on open water.



175 - 300 FOURSTROKE

AWESOME BOATING

The new Mercury FourStrokes are precision engineered with advanced technology to optimize all aspects of performance and reliability. The robust V-8 4.6-liter and V-6 3.4-liter engines deliver superior hole shot, top speed and fuel efficiency. These new FourStrokes also provide unsurpassed dampening of sound and vibration for a superior boating experience.







ADAPTIVE SPEED CONTROL

ASC allows boaters to maintain engine speed (rpm) regardless of load or condition changes – such as rough water, tight turns, tow sports and lower speeds on plane – without having to frequently adjust throttle position, a first for the outboard industry.

IDLE CHARGE

Idle Charge battery-management prevents boaters from draining their batteries while operating multiple electronic devices. When battery voltage is reduced, the engine will automatically increase idle rpm to boost alternator output and recharge low batteries to the proper level.

TOP COWL SERVICE DOOR

For easy and simple engine oil checks and oil fills, just pop open the new Service Door on top of the cowl. A single push opens the watertight door for access to the dipstick, service decal, and carrying handle.



GREAT FOR REPOWER

The V-8 and V-6 FourStrokes mount on 26-inch centers, which helps them fit a broader range of transoms – ideal for simple, seamless repower applications. Available with mechanical or digital controls, boaters can choose between hydraulic (standard) or power steering (optional).





MERCURY

FOURSTROKE



75 / 90 / 115 FOURSTROKE

MORE TORQUE. $\overline{MOREPOWER}$.

Less weight – nearly 20 pounds less than its closest four-stroke competitor - and high displacement mean these 2.1-liter FourStroke models generate abundant torque and immediate power. Because they don't have to work as hard as heavier engines or those with lower displacement, these outboards help boats plane faster, accelerate quicker and provide optimal fuel efficiency at cruising speed.

COMMAND THRUST

The larger Command Thrust gearcase available for 115hp and 90hp outboards, combined with a biggerdiameter, V-6-class propeller, can lift a heavy boat onto plane more easily and hold it there at lower speeds without impacting top speed. A left-hand rotation Command Thrust gearcase for the 115hp enables dual engine installations.





40 / 50 / 60 FOURSTROKE

WELCOME TO EFFICIENCY

Welcome to turnkey boating. Mercury Electronic Fuel Injection delivers reliable starts, improved fuel efficiency, instant throttle response and protection against low-quality-fuel problems. Enjoy mid-size muscle: A compact, single-overhead-cam design and long piston stroke delivers more low-end torque for excellent acceleration, even when pushing a heavy load.

COMMAND THRUST

Available Command Thrust gearcase for 60 / 50 / 40hp FourStroke models offers more control, improved hole shot and enhanced midrange power. The combination of a gearcase that sits deeper in the water, a bigger prop with 20 percent more blade surface, and lower gear ratio provide unmatched thrust, maneuverability and boat lift.

THE BIG TILLER

A longer tiller incorporates convenient power trim and ignition switches, the shift lever is close at hand, and an optional digital troll control adjusts engine speed as low as 700 rpm in 10-rpm increments.



25 / 30 FOURSTROKE

SEASON TO SEASON

Electronic Fuel Injection plus extra displacement for more low-end torque help these FourStroke models pack a real punch. And they're engineered to deliver reliable performance season after season. For a perfect getaway on the water, you can count on Mercury FourStrokes.

1600 Fury




BATTERY-FREE

Reliable starts – cold or hot – with manual or turnkey starting. Every time. This battery-free system saves weight and space in the boat. Fuel efficiency and throttle response are optimized.

HANDY TILLER

Our tiller design combines steering, throttle, shift and stop in the twist grip. The tiller even controls the tilt function for on-the-go adjustments to shallow-water positions.





AMBIDEXTROUS TILLER

The new center-mounted tiller provides simple horizontal adjustment and reversible throttle grip rotation for right or left-hand operation. Vertical down-stop is also adjustable, so you can dial in this tiller to fit the boat and the operator's reach and preference. The large shift lever is located forward on the tiller for easy operation, and sets a new standard with more features and functions making boating easier and more comfortable.

LESS WEIGHT, MORE TORQUE

A new low-friction, single overhead-cam powerhead delivers greater torque. Meanwhile, overall weight is decreased by 10 pounds – a significant reduction that makes a big difference on small boats. These are the quickest, fastest and strongest outboards in the category.





15 PROKICKER

BETTER TROLLING

Get all the power you need to control bigger boats. Electronic Fuel Injection enables precise fuel metering for smooth operation all day at the lowest trolling speeds. Standard power tilt adds convenience. Exclusive centering straps, available on tiller handle models, automatically straighten and lock the outboard in place when tilted up to protect the transom bracket.



EASY TO START

Enjoy no-hassle starting. Automatic decompression reduces the pulling force required to pull-start the engine. Mercury's 9.9hp and 8hp models have optimized ignition timing for smooth slow-speed acceleration, a benefit when trolling. A three-position choke with no primer and a richer idle air/fuel mix allow the engine to warm up faster (tiller handle models).



IERCURY IERCURY

COMMAND THRUST

Move heavier boats with more control. The Command Thrust gearcase available for 9.9hp FourStroke models offers a deeper gearcase, 22 percent more prop blade area and a 2.42:1 gear ratio for better boat control while fishing. An oversized anti-ventilation plate prevents air from being drawn into the prop, which increases efficiency.

9.9 PROKICKER

ULTIMATE CONTROL

Designed as the ultimate trolling auxiliary with a Command Thrust gearcase and a four-blade, high-thrust propeller matched to a 2.42:1 gear ratio. Standard power tilt adds convenience. Exclusive centering straps, available on tiller handle models, automatically straighten and lock the outboard in place when tilted up to protect the transom bracket during high-speed runs and trailering.





2.5 - 6 fourstroke

8/9.9 fourstroke

| Horsepower | 2.5 | 3.5 | 4 | 5 | 6 | 8 | 9.9 | 9.9 CT | 9.9 ProKicker |
|--------------|------------------|--------------------------------|--------------------------------------|---|--------------------------------------|--|---|--|--|
| WOT RPM | 4500-5500 | 5000-6000 | 4500-5500 | 4500-5500 | 5000-6000 | 5000-6000 | 5000-6000 | 5000-6000 | 5000-6000 |
| Engine Type | 1 cylinder | 1 cylinder | 1 cylinder | 1 cylinder | 1 cylinder | Inline-2 | Inline-2 | Inline-2 | Inline-2 |
| Displacement | 5.2 cu in (85cc) | 5.2 cu in (85cc) | 7.5 cu in (123cc) | 7.5 cu in (123cc) | 7.5 cu in (123cc) | 12.8 cu in (208cc) | 12.8 cu in (208cc) | 12.8 cu in (208cc) | 12.8 cu in (208cc) |
| Induction | 2-valve, pushrod | 2-valve, pushrod | 2-valve, pushrod | 2-valve, pushrod | 2-valve, pushrod | 4-valve, SOHC | 4-valve, SOHC | 4-valve, SOHC | 4-valve, SOHC |
| Starting | Manual | Manual | Manual | Manual | Manual | Electric or manual | Electric or manual | Electric or manual | Electric or manual |
| Gear Ratio | 2.15:1 | 2.15:1 | 2.15:1 | 2.15:1 | 2.15:1 | 2.08:1 | 2.08:1 | 2.42:1 | 2.42:1 |
| Alternator | N/A | N/A | N/A | Sailpower 4 amp (50 watt) lighting and charging | N/A | 6 amp (76 watt) on electric-start models | 6 amp (76 watt) on electric-start models | 6 amp (76 watt) on electric-start models | 6 amp (76 watt) on electric-start models |
| Trim System | 4 position | 4 position | 6 position w/ shallow water drive | 6 position w/ shallow water drive | 6 position w/ shallow water drive | Ratcheting w/ shallow water drive | Ratcheting w/ shallow water drive | Ratcheting w/ shallow water drive | Power tilt |
| Dry Weight* | 41lbs (18 kg) | 41lbs (18 kg) | 57lbs (26kg) | 57lbs (26kg) | 57lbs (26kg) | 84lbs (38kg) | 84lbs (38kg) | 96lbs (44kg) | 108lbs (49kg) |
| Steering | 360° tiller | 360° tiller | Tiller | Tiller | Tiller | Tiller | Remote or tiller | Remote or tiller | Remote or tiller |
| Shaft Length | 15 in (381mm) | 15 in (381mm) 20 in (508mm) | 15 in (381mm) 20 in (508mm) | 15 in (381mm) 20 in (508mm) 25 in (635mm) | 15 in (381mm) 20 in (508mm) | 15 in (381mm) 20 in (508mm) | 15 in (381mm) 20 in (508mm) 25 in (635mm) | 20 in (508mm) 25 in (635mm) | 20 in (508mm) 25 in (635mm) |

15/20 fourstroke

| Horsepower | 15 EFI | 15 EFI ProKicker | 20 EFI |
|--------------|--|--|--|
| WOT RPM | 5700-6200 | 5700-6200 | 5700-6200 |
| Engine Type | Inline-2 | Inline-2 | Inline-2 |
| Displacement | 20.3 cu in (333cc) | 20.3 cu in (333cc) | 20.3 cu in (333cc) |
| Induction | 4-Valve, SOHC | 4-Valve, SOHC | 4-Valve, SOHC |
| Starting | Manual or electric | Electric w/manual backup | Manual or electric |
| Gear Ratio | 2.15:1 | 2.15:1 | 2.15:1 |
| Alternator | 12 amp (145 watt) electric-start models | 12 amp (145 watt) electric-start models | 12 amp (145 watt) electric-start models |
| Trim System | 6 manual or power tilt | Power tilt | 6 manual or power tilt |
| Dry Weight* | 99lbs (45kg) | 122lbs (55kgs) | 99lbs (45kg) |
| Steering | Tiller or remote | Tiller or remote | Tiller or remote |
| Shaft Length | 15in (381mm) 20in (508mm) | 20in (508mm) 25in (635mm) | 15in (381mm) 20in (508mm) |

25 / 30 fourstroke

| MERCURY | Horsepower | 25 EFI | 30 EFI |
|---------|--------------|--------------------------------|----------------------------------|
| | WOT RPM | 5000-6000 | 5250-6250 |
| | Engine Type | Inline-3 | Inline-3 |
| | Displacement | 32.1 cu in (526cc) | 32.1 cu in (526cc) |
| | Induction | 6-valve, SOHC | 6-valve, SOHC |
| | Starting | Electric(turn-key) or manual | Electric (turn-key) or manual |
| | Gear Ratio | 1.92:1 | 1.92:1 |
| | Alternator | 15 amp (186 watt) | 15 amp (186 watt) |
| | Trim System | Manual or power trim | Gas assist or power trim |
| - | Dry Weight* | 157lbs (71kg) | 172lbs (78kg) |
| | Steering | Remote or tiller | Remote or tiller |
| | Shaft Length | 15 in (381mm) 20 in (508mm) | 15 in (381mm) 20 in (508mm) |

40/50/60 fourstroke

| MERCURY |
|---------|
| |
| |
| |
| - |

| | Horsepower | 40 Carburetor | 40 | 40 CT | 50 | 50 CT | 60 | 60 CT |
|---|--------------|--------------------------------|-----------------------------------|---------------------|---------------------|----------------------|---------------------|-------------------------------|
| , | WOT RPM | 5500-6000 | 5500-6000 | 5500-6000 | 5000-6000 | 5500-6000 | 5500-6000 | 5500-6000 |
| | Engine Type | Inline-3 | Inline-3 | Inline-4 | Inline-4 | Inline-4 | Inline-4 | Inline-4 |
| | Displacement | 45.6 cu in (747cc) | 45.6 cu in (747cc) | 60.8 cu in (995cc) | 60.8 cu in (995cc) | 60.8 cu in (995cc) | 60.8 cu in (995cc) | 60.8 cu in (995cc) |
| | Induction | 6-valve, SOHC | 6-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC |
| | Starting | Manual | Electric (turn-key) | Electric (turn-key) | Electric (turn-key) | Electric (turn-key) | Electric (turn-key) | Electric (turn-key) |
| | Gear Ratio | 2.00:1 | 2.00:1 | 2.33:1 | 1.83:1 | 2.33:1 | 1.83:1 | 2.33:1 |
| | Alternator | 18 amp (226 watt) | 18 amp (226 watt) | 18 amp (226 watt) | 18 amp (226 watt) | 18 amp (226 watt) | 18 amp (226 watt) | 18 amp (226 watt) |
| | Trim System | Gas assist trim | Gas assist or power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt |
| | Dry Weight* | 204lbs (93kg) | 216lbs (98kg) | 260lbs (118kg) | 247lbs (112kg) | 260lbs (118kg) | 247lbs (112kg) | 260lbs (118kg) |
| | Steering | Tiller | Remote or tiller | Remote or tiller | Remote or tiller | Remote or Big tiller | Remote or tiller | Remote or Big tiller |
| | Shaft Length | 15 in (381mm) 20 in (508mm) | 15 in (381mm) 20 in (508mm) | 20 in (508mm) | 20 in (508mm) | 20 in (508mm) | 20 in (508mm) | 20 in (508mm 25 in (635mm) |

75/90/115 fourstroke



| Horsepower | 75 | 90 | 90 CT | 115 | 115 CT |
|--------------|----------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| WOT RPM | 4500-5500 | 5000-6000 | 5000-6000 | 5000-6000 | 5000-6000 |
| Engine Type | Inline-4 | Inline-4 | Inline-4 | Inline-4 | Inline-4 |
| Displacement | 126 cu in (2.1L) | 126 cu in (2.1L) | 126 cu in (2.1L) | 126 cu in (2.1L) | 126 cu in (2.1L) |
| Induction | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC |
| Starting | SmartStart electric | SmartStart electric | SmartStart electric | SmartStart electric | SmartStart electric |
| Gear Ratio | 2.07:1 | 2.07:1 | 2.38:1 | 2.07:1 | 2.38:1 |
| Alternator | 35 amp (441 watt) | 35 amp (441 watt) | 35 amp (441 watt) | 35 amp (441 watt) | 35 amp (441 watt) |
| Trim System | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt |
| Dry Weight* | 359lbs (163kg) | 359lbs (163kg) | 363lbs (165kg) | 359lbs (163kg) | 363lbs (165kg) |
| Steering | Remote or Big Tiller | Remote or Big Tiller | Remote or Big Tiller | Remote or Big Tiller | Remote or Big Tiller |
| Shaft Length | 20 in (508mm) | 20 in (508mm) 25 in (635mm) |





FACTORY-BACKED

Every Mercury FourStroke comes with class-leading corrosion protection and an industry-exclusive three-year limited corrosion warranty.





150 fourstroke

| 100101110111 | | | | | |
|--------------|------------------------------|--|--|--|--|
| Horsepower | 150 | | | | |
| WOT RPM | 5000-5800 | | | | |
| Engine Type | Inline-4 | | | | |
| Displacement | 183 cu. in. (3.0L) | | | | |
| Induction | 8-valves, SOHC | | | | |
| Starting | SmartStart Electric | | | | |
| Gear Ratio | 1.92:1 | | | | |
| Alternator | 60 amp (756 watt) | | | | |
| Trim System | Power trim and tilt | | | | |
| Dry Weight* | 455lbs (206kg) | | | | |
| Steering | Remote or Big Tiller | | | | |
| Shaft Length | 20in (508mm) 25in (635mm) | | | | |





Factory-backed

Every Mercury FourStroke comes with class-leading corrosion protection and an industry-exclusive three-year limited corrosion warranty.



Active Trim

Active Trim makes boating easier and more enjoyable by automatically trimming outboard and sterndrive engines. Active Trim simplifies boat operation while improving engine performance and decreasing fuel costs.

Active Trim is compatible with all current SmartCraft-capable Mercury outboards (40hp and above).



VesselView Mobile

VesselView Mobile allows boaters to use a mobile device (smartphone or tablet) to connect with their Mercury outboard or sterndrive engine(s). The plug-and-play module connects to your device via Bluetooth, providing quick, convenient access to your engine's data.

VesselView Mobile is compatible with all SmartCraft-capable Mercury outboards (2004 and newer, 40hp and above).



175 - 300 fourstroke

| Horsepower | 175 | 200 | 225 | 250 | 300 |
|--------------|--|---|---|---|--|
| WOT RPM | 5000-5800 | 5000-5800 | 5200-6000 | 5200-6000 | 5200-6000 |
| Engine Type | V-6 | V-6 | V-6 | V-8 | V-8 |
| Displacement | 209 cu. in. (3.4L) | 209 cu. in. (3.4L) | 209 cu. in. (3.4L) | 279 cu. in. (4.6L) | 279 cu. in. (4.6L) |
| Induction | 24-valve DOHC | 24-valve DOHC | 24-valve DOHC | 32-valve DOHC | 32-valve DOHC |
| Starting | SmartStart electric | SmartStart electric | SmartStart electric | SmartStart electric | SmartStart electric |
| Gear Ratio | 1.85:1 | 1.85:1 | 1.85:1 | 1.75:1 | 1.75:1 |
| Alternator | 85 amp (1071 watt) | 85 amp (1071 watt) | 85 amp (1071 watt) | 85 amp (1071 watt) | 85 amp (1071 watt) |
| Trim System | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt |
| Dry Weight* | 475lbs (215kg) | 475lbs (215kg) | 475lbs (215kg) | 527lbs (239kg) | 527lbs (239kg) |
| Steering | Hydraulic (standard) Power (option)) Big Tiller (option) | Hydraulic (standard) Power (option) Big Tiller (option) | Hydraulic (standard) Power (option) Big Tiller (option) | Hydraulic (standard) Power (option) Big Tiller (option) | Hydraulic (standard) Power (option) |
| Shaft Length | 20in (508mm) 25in (635mm) | 20in (508mm) 25in (635mm) | 20in (508mm) 25in (635mm) 30in (762mm) | 20in (508mm) 25in (635mm) 30in (762mm) | 20in (508mm) 25in (635mm) |

COLOR CHOICES

Three shades of white - Cold Fusion White, Warm Fusion White and Pearl Fusion White - and traditional Phantom Black are available on 200 though 300hp Mercury FourStroke outboards.





Phantom Black





Pearl Fusion White





Warm Fusion White






Cold Fusion White



ACCENT PANEL COLORS

For ultimate personalization of 175 through 300hp Mercury FourStrokes, four colors of factory-painted accent panels are available as kits. The panels are made from thin and durable polycarbonate that adhere firmly and provide color harmonization with a wide variety of boat colors.
























NEVER RUN OUT OF JUICE

A powerful alternator provides net charging output of 20 amps at idle and 85 amps total at wide open throttle. Additionally, Idle Charge battery-management technology automatically increases idle rpm to boost alternator output and recharge low batteries to the proper level.



THE COWL STAYS ON

For easy oil checks and fills just pop open the new watertight Service Door on top of the cowl. Even smarter, at start-up the optional electronic oil-level sensor automatically alerts you to low oil level.

115 / 150 PRO XS

TUNED TO PERFORM

On freshwater or saltwater – compact bass rigs or flats skiffs, pontoons or multi-species boats – four-cylinder Mercury Pro XS models are tuned to take mid-size boats to the limit. Engine controls are calibrated for stronger hole shot and higher rpm. Stiffer high-performance motor mounts on the 150 deliver better high-speed handling. It's the look and performance of a champion, with bold Pro XS graphics.

BEST-IN-CLASS ACCELERATION

The lowest weight and highest displacement in the category contribute to unmatched hole shot on a wide variety of boats. The 150 Pro XS features new Transient Spark technology to optimize spark timing and boost hole shot torque, as well as a higher gear ratio that transmits more torque to the prop shaft.

ENGINEERED TO PERFORM

Higher wide-open-throttle rpm range permits use of a wider selection of prop pitches, so you can prop for hole shot or top speed. The 150 Pro XS features a proven, performance-inspired 4.8-inch diameter gearcase with front water pickups and a 2.08:1 gear ratio for true dialed-in performance.



SMART CHARGING

The best-in-class alternator output on the 150 Pro XS keeps up with marine electronics and accessories. New Idle Charge low-voltage battery-management automatically boosts idle speed and alternator output to recharge boat batteries to the proper level.





The 115 Pro XS is available with our exclusive Command Thrust gearcase, which features a larger diameter torpedo and prop and creates a bigger footprint in the water. This offers boaters more leverage to control their boats and greater ability to get heavily loaded boats on plane and keep them there.



INCOME.

115 pro xs

| Horsepower | 115 | 115 CT | |
|--------------|--------------------------------|--------------------------------|--|
| WOT RPM | 5300-6300 | 5300-6300 | |
| Engine Type | Inline-4 | Inline-4 | |
| Displacement | 126 cu in (2.1L) | 126 cu in (2.1L) | |
| Induction | 8-valve, SOHC | 8-valve, SOHC | |
| Starting | SmartStart electric | SmartStart electric | |
| Gear Ratio | 2.07:1 | 2.38:1 | |
| Alternator | 35 amp (441 watt) | 35 amp (441 watt) | |
| Trim System | Power trim and tilt | Power trim and tilt | |
| Dry Weight* | 359lbs (163kg) | 363lbs (165kg) | |
| Steering | Remote or Big Tiller | Remote or Big Tiller | |
| Shaft Length | 20 in (508mm) 25 in (635mm) | 20 in (508mm) 25 in (635mm) | |



150 pro xs

| Horsepower | 150 |
|--------------|------------------------------|
| WOT RPM | 5200-6000 |
| Engine Type | Inline-4 |
| Displacement | 183 cu. in. (3.0L) |
| Induction | 8-valves, SOHC |
| Starting | SmartStart electric |
| Gear Ratio | 2.08:1 |
| Alternator | 60 amp (756 watt) |
| Trim System | Power trim and tilt |
| Dry Weight* | 456lbs (207kg) |
| Steering | Remote or Big Tiller |
| Shaft Length | 20in (508mm) 25in (635mm) |



Active Trim

Active Trim makes boating easier and more enjoyable by automatically trimming outboard and sterndrive engines. Active Trim simplifies boat operation while improving engine performance and decreasing fuel costs.

Active Trim is compatible with all current SmartCraft-capable Mercury outboards (40hp and above).



VesselView Mobile

VesselView Mobile allows boaters to use a mobile device (smartphone or tablet) to connect with their Mercury outboard or sterndrive engine(s). The plug-and-play module connects to your device via Bluetooth, providing quick, convenient access to your engine's data.

VesselView Mobile is compatible with all SmartCraft-capable Mercury outboards (2004 and newer, 40hp and above).

VesselView Link

VesselView Link connects all features offered by SmartCraft to compatible Lowrance and Simrad displays, placing the complete VesselView information suite and control capability on your main helm display.

VesselView Link is compatible with all SmartCraft-capable Mercury outboards (2004 and newer, 40hp and above).



DTS Hot Foot

A Digital Throttle & Shift (DTS) Hot Foot pedal allows you to keep both hands on the wheel during high-speed runs. DTS provides precise handling, seamlessly connects with compatible displays, and delivers instant response and total control with no hesitation.

DTS Hot Foot pedal is compatible with 200 - 300hp Pro XS outboards.






175 – 300 **pro xs**

| Horsepower | 175 | 200 | 225 | 250 | 300 |
|--------------|---|---|---|---|--|
| WOT RPM | 5400-6000 | 5600-6200 | 5600-6200 | 5600-6200 | 5600-6200 |
| Engine Type | V-6 | V-8 | V-8 | V-8 | V-8 |
| Displacement | 209 cu. in. (3.4L) | 279 cu. in. (4.6L) | 279 cu. in. (4.6L) | 279 cu. in. (4.6L) | 279 cu. in. (4.6L) |
| Induction | 24-valve DOHC | 32-valve DOHC | 32-valve DOHC | 32-valve DOHC | 32-valve DOHC |
| Starting | SmartStart electric | SmartStart electric | SmartStart electric | SmartStart electric | SmartStart electric |
| Gear Ratio | 1.85:1 | 1.75:1 | 1.75:1 | 1.75:1 | 1.75:1 |
| Alternator | 85 amp (1071 watt) | 85 amp (1071 watt) |
| Trim System | Power trim and tilt | Power trim and tilt |
| Dry Weight* | 470lbs (213kg) | 505lbs (229kg) | 505lbs (229kg) | 505lbs (229kg) | 505lbs (229kg) |
| Steering | Hydraulic (standard) Power (option) Big Tiller (option) | Hydraulic (standard) Power (option) |
| Shaft Length | 20in (508mm) 25in (635mm) | 20in (508mm) 25in (635mm) | 20in (508mm) 25in (635mm) | 20in (508mm) 25in (635mm) | 20in (508mm) 25in (635mm) |

PRO BLACK ACCENT PANEL

Make a statement by personalizing your Pro XS outboard with a factory-painted Pro Black accent panel. Made of thin and durable polycarbonate that adheres firmly to the cowl, the panel is available from your local Mercury dealer for 175-300hp Pro XS models.











FACTORY-BACKED

Every Mercury Pro XS comes with class-leading corrosion protection and an industry-exclusive three-year limited corrosion warranty.







REDUCE YOUR FUEL COST

Advanced Range Optimization (ARO) calibration utilizes closed-loop fuel control to precisely adjust the fuel mixture and deliver the best possible efficiency.

200-300 seapro

The new Mercury V-8 and V-6 SeaPro outboard models bring more of everything to the job – more displacement, more power, more efficiency and more durability. The impressive muscle of our new V-8 4.6-liter and V-6 3.4-liter powerheads is specifically designed for commercial duty and delivers our best-ever fuel economy. The combination of ample torque and low weight make these engines ideal for heavily loaded boats.

LIGHT AND COMPACT

Mercury engineers strategically trimmed weight to produce some of the lightest engines in their class – by up to 30 pounds. V-8 and V-6 SeaPro models mount on 26-inch centers and are ideal for a broad range of applications, including simple, seamless repower rigging.

STAY READY

The new 200-300hp SeaPro outboards feature a high-capacity alternator that cranks out a robust 20 amps of charging power at idle.



SMOOTH OPERATOR

300hp AMS models are available with joystick piloting, electro-hydraulic power steering, and Mercury's exclusive Advanced MidSection (AMS). The Advanced MidSection virtually eliminates vibration from being transmitted to the boat, while joystick piloting provides maximum levels of control and maneuverability.

MAXIMUM DURABILITY

V-8 and V-6 SeaPro outboards feature a heavy-duty gearcase that is validated at three times the lifespan of a recreational gearcase and slips easily through the water, decreasing the workload on the engine. Commercial calibration allows the engine to reach maximum torque well below peak rpm – more power with less stress on the motor.

TOP COWL SERVICE DOOR

The Top Cowl Service Door, an industry-exclusive feature, simplifies routine maintenance with easy oil checks and oil fills without removing the cowl. A single push opens the watertight door for access to the dipstick, service decal, and carrying handle.

EASY TO MAINTAIN

Hour-based maintenance decal is conveniently located under the cowl, providing a quick overview of routine maintenance intervals. Regular maintenance points are color-coded and accessible by removing the top cowl only.



MADE FOR WORK

The 150 SeaPro is built to deliver loads of torque while still providing superior durability and greater longevity. Its heavy-duty gearcase is validated at three times the lifespan of a recreational gearcase.

75 - 150 seapro

No family works harder than SeaPro, and Mercury's midrange lineup of 75 through 150hp in-line four-cylinder commercial-grade outboards is ready to go wherever and whenever you are. The rugged and ultra-durable 3.0-liter 150hp and its feisty 2.1-liter brothers deliver great torque for less stress on the powerhead. They're all built to handle the demands and long hours of commercial applications, yet they're light and fuel-efficient.

TOUGH INSIDE AND OUT

The upper motor mounts are designed to be two times stiffer than recreational models to maximize durability. Their longevity makes them ideally suited for the demands and rigors of commercial applications. Mercury's proprietary XK360 low-copper aluminum alloy leads the industry in corrosion resistance.



KEEP DOWNTIME DOWN

Easy-access fuel filter and no-spill oil-change system combine to help keep downtime to a minimum. Hourbased maintenance decal is conveniently located under the cowl, providing a quick overview of routine maintenance intervals.

BIGGER FOOTPRINT

A heavy-duty Command Thrust gearcase on 75-115 SeaPro outboards permits use of an oversized prop, sits deeper in the water and incorporates a specific gearcase ratio – all designed to improve handling and easily lift heavier boats.



REPOWER WITH SEAPRO

SeaPro models perfect for repower on older boats not originally designed for the weight of heavier four-stroke outboards. Work smarter with the latest technology, improved fuel economy and greater reliability.





COMMAND THRUST

A rugged Command Thrust gearcase permits use of an oversized prop, sits deeper in the water and incorporates a specific gearcase ratio. Its larger torpedo, combined with a bigger-diameter prop, can lift a heavy boat onto plane more easily and hold it there at lower speeds.

40/60 seapro

Designed to tackle the toughest jobs season after season, the 40 and 60hp SeaPro models are validated to three times the engine life of a recreational engine. A compact, single-overhead-cam design and long piston stroke delivers more low-end torque for stout power, even when pushing a heavy load. Electronic Fuel Injection (EFI) delivers reliable starts, improved fuel efficiency, and protection against problems from poor fuel quality.

COMMERCIAL GRADE

A specific commercial calibration allows the engine to reach maximum torque well below peak rpm more power with less stress on the motor. The upper motor mounts are designed to be two times stiffer than recreational models to maximize durability, and Mercury's proprietary XK360 low-copper aluminum alloy leads the industry in corrosion resistance.



NO-MESS MAINTENANCE

Clear information for routine maintenance is provided on a decal under the cowl, with a QR code for smartphones that links to additional instruction. A new drain hose removes oil from the filter for no-mess maintenance, and there's a convenient freshwater flush fitting.

15 seapro

The rugged new 15hp SeaPro is designed and built to take on big jobs in smaller boats. New twin-cylinder powerhead with Electronic Fuel Injection (EFI) delivers quick starts and outstanding torque to move heavy loads.

AMBIDEXTROUS TILLER

The new center-mounted tiller features simple horizontal adjustment and reversible throttle grip rotation for left- or right-hand operation, and an auto-return spring takes the throttle to idle when the grip is released.





15 seapro

| Horsepower | 15 EFI |
|--------------|--|
| WOT RPM | 4500-5500 |
| Engine Type | Inline-2 |
| Displacement | 20.3 cu in (333cc) |
| Induction | 4-Valve, SOHC |
| Starting | Manual |
| Gear Ratio | 2.15:1 |
| Alternator | 12 amp (145 watt) w/ electric start kit |
| Trim System | 6 manual |
| Dry Weight* | 105lbs (47.5kgs) |
| Steering | Tiller or remote |
| Shaft Length | 15in (381mm) 20in (508mm) |



40/60 seapro

| Horsepower | 40 | 60 | |
|--------------|--|--|--|
| WOT RPM | 4500-5500 | 4500-5500 | |
| Engine Type | Inline-4 | Inline-4 | |
| Displacement | 60.8 cu in (995cc) | 60.8 cu in (995cc) | |
| Induction | 8-valve, SOHC | 8-valve, SOHC | |
| Starting | Electric (turn-key) | Electric (turn-key) | |
| Gear Ratio | 2.33:1 | 2.33:1 | |
| Alternator | 18 amp (226 watt) | 18 amp (226 watt) | |
| Trim System | Gas assist or power trim and tilt | Gas assist or power trim and tilt | |
| Dry Weight* | 260lbs (118kg) | 260lbs (118kg) | |
| Steering | Remote or Big Tiller | Remote or Big Tiller | |
| Shaft Length | 20in (508mm) 22.5in (571.5mm) 25in (635mm) | 20in (508mm) 22.5in (571.5mm) 25in (635mm) | |





FACTORY-BACKED

Every Mercury SeaPro comes with class-leading corrosion protection and an industry-exclusive three-year limited corrosion warranty.



5470

Active Trim

Active Trim makes boating easier and more enjoyable by automatically trimming outboard and sterndrive engines. Active Trim simplifies boat operation while improving engine performance and decreasing fuel costs.

Active Trim is compatible with all current SmartCraft-capable Mercury outboards (40hp and above).



VesselView Mobile

VesselView Mobile allows boaters to use a mobile device (smartphone or tablet) to connect with their Mercury outboard or sterndrive engine(s). The plug-and-play module connects to your device via Bluetooth, providing quick, convenient access to your engine's data.

VesselView Mobile is compatible with all SmartCraft-capable Mercury outboards (2004 and newer, 40hp and above).

Joystick Piloting

300hp SeaPro AMS outboards are available with Joystick Piloting for Outboards. Joystick Piloting is designed for dual, triple and quad SeaPro-powered vessels and personalized for each boat model. Mercury Joystick Piloting was the industry's first joystick system for outboards, and it remains the best-selling marine joystick system.

Joystick Piloting is optional on 300hp SeaPro AMS outboards.

Big Tiller

Optional Big Tiller offers optimal control for 40 - 250hp SeaPro outboards. Longer tiller grip incorporates a convenient power trim switch, shift lever is close at hand, and an optional digital troll control adjusts engine speed in 10-rpm increments.

Big Tiller is available on 40 - 250hp SeaPro outboards.





75 – 115 seapro

| Horsepower | 75 | 90 | 115 |
|--------------|----------------------|--------------------------------|--------------------------------|
| WOT RPM | 5000-5500 | 5000-5500 | 5000-5500 |
| Engine Type | Inline-4 | Inline-4 | Inline-4 |
| Displacement | 126 cu in (2.1L) | 126 cu in (2.1L) | 126 cu in (2.1L) |
| Induction | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC |
| Starting | SmartStart electric | SmartStart electric | SmartStart electric |
| Gear Ratio | 2.38:1 | 2.38:1 | 2.38:1 |
| Alternator | 35 amp (441 watt) | 35 amp (441 watt) | 35 amp (441 watt) |
| Trim System | Power trim and tilt | Power trim and tilt | Power trim and tilt |
| Dry Weight* | 363lbs (165kg) | 363lbs (165kg) | 363lbs (165kg) |
| Steering | Remote or Big Tiller | Remote or Big Tiller | Remote or Big Tiller |
| Shaft Length | 20 in (508mm) | 20 in (508mm) 25 in (635mm) | 20 in (508mm) 25 in (635mm) |



150 seapro

| Horsepower | 150 |
|--------------|--------------------------------|
| WOT RPM | 4800-5300 |
| Engine Type | 1-4 |
| Displacement | 183 cu. in. (3.0L) |
| Induction | 8-valve, SOHC |
| Starting | SmartStart electric |
| Gear Ratio | 1.92:1 |
| Alternator | 60 amp (756 watt) |
| Trim System | Power trim and tilt |
| Dry Weight* | 455lbs (206kg) |
| Steering | Remote or Big Tiller |
| Shaft Length | 20 in (508mm) 25 in (635mm) |

200 – 300 seapro



| Horsepower | 200 | 225 | 250 | 300 | 300 AMS |
|--------------|--|--|---|--|--|
| WOT RPM | 4600-5400 | 4800-5600 | 4800-5600 | 4800-5600 | 4800-5600 |
| Engine Type | V-6 | V-8 | V-8 | V-8 | V-8 |
| Displacement | 209 cu. in. (3.4L) | 279 cu. in. (4.6L) | 279 cu. in. (4.6L) | 279 cu. in. (4.6L) | 279 cu. in. (4.6L) |
| Induction | 24-valve DOHC | 32-valve DOHC | 32-valve DOHC | 32-valve DOHC | 32-valve DOHC |
| Starting | SmartStart Electric | SmartStart Electric | SmartStart Electric | SmartStart Electric | SmartStart Electric |
| Gear Ratio | 1.85:1 | 1.75:1 | 1.75:1 | 1.75:1 | 1.75:1 |
| Alternator | 85 amp (1071 watt) | 85 amp (1071 watt) | 85 amp (1071 watt) | 85 amp (1071 watt) | 115 amp (1449 watt) |
| Trim System | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt |
| Dry Weight* | 483lbs (220kg) | 527lbs (239kg) | 527lbs (239kg) | 527lbs (239kg) | 600lbs (272kg) |
| Steering | Hydraulic (standard) Power (option)) Big Tiller (option) | Hydraulic (standard) Power (option)) Big Tiller (option) | Hydraulic (standard) Power (option) Big Tiller (option) | Hydraulic (standard) Power (option) | Electro-hydraulic power steering |
| Shaft Length | 20in (508mm) 25in (635mm) | 20in (508mm) 25in (635mm) 30in (762mm) | 20in (508mm) 25in (635mm) 30in (762mm) | 20in (508mm) 25in (635mm) 30in (762mm) | 20in (508mm) 25in (635mm) 30in (762mm) |







200 optimax® sportjet®

The V-6 SportJet brings a level of lightweight performance to the inboard jet category. Maneuver through the shallows with ease and rely on the power and speed available for all types of boating fun, including tubing and skiing. Our award-winning OptiMax two-stroke Direct Injection technology provides instant turnkey starting, nosmoke operation, outstanding fuel economy and an excellent power-to-weight ratio. It's also easy to use and maintain.

Choose from **three intake grate options** to match your water conditions and intended use: Standard aluminum grate for general use, stainless-grate for gravel bottoms, and the spring-loaded Hydro-Surge grate for automatic weed cleanout from the jet intake.





25-80 fourstroke jet

Tackle your adventure with a Mercury Jet outboard, available in a size to fit almost any boat made for shallow water, including drifters, jons, sleds and shallow-vees. All Mercury Jet outboard models feature an efficient FourStroke powerhead designed to be as light as possible, a key advantage in shallow water situations.

Our **stainless impellers improve** performance and withstand harsh, abrasive debris that can be drawn through the pump, such as sand and shells. That ability adds to long-term durability and reliability.

| Horsepower | 25 Jet | 35 Jet | 40 Jet | 65 Jet | 80 Jet | 200 SportJet |
|--------------|-------------------------------|----------------------|----------------------|--------------------------|--------------------------|-------------------------------------|
| WOT RPM | 5000-5500 | 5000-6000 | 5000-6000 | 5000-6000 | 5000-6000 | 5150-5650 |
| Engine Type | I-3 | 1-4 | 1-4 | 1-4 | 1-4 | V-6 (60° vee) |
| Displacement | 32.1 cu in (526cc) | 60.8 cu in (995cc) | 60.8 cu in (995cc) | 126 cu in (2.1L) | 126 cu in (2.1L) | 153 cu in (2.5L) |
| Induction | 6-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 8-valve, SOHC | 2-stage Direct Fuel Injection (DFI) |
| Starting | Electric (turn-key) or manual | Electric (turn-key) | Electric (turn-key) | SmartStart electric | SmartStart electric | Electric (turn-key) |
| Gear Ratio | Jet drive | Jet drive | Jet drive | Jet drive | Jet drive | Jet drive |
| Alternator | 15 amp (186 watt) | 18 amp (226 watt) | 18 amp (226 watt) | 35 amp (441 watt) | 35 amp (441 watt) | 60 amp (756 watt) |
| Trim System | Gas assist or power trim | Power trim and tilt | Power trim and tilt | Power trim and tilt | Power trim and tilt | N/A |
| Dry Weight* | 186lbs (84kg) | 267lbs (121kg) | 267lbs (121kg) | 378lbs (171kg) | 378lbs (171kg) | 367lbs (166kg) |
| Steering | Remote or tiller | Remote or tiller kit | Remote or tiller kit | Remote or Big Tiller kit | Remote or Big Tiller kit | Remote |
| Shaft Length | Jet drive | Jet drive | Jet drive | Jet drive | Jet drive | Jet drive |

^{*}Dry weight specification is for the lightest-version model. Note: Due to our constant efforts to offer the finest products available, we reserve the right to change specifications without notice.

Visit MercuryMarine.com or your Mercury Authorized Dealer for more engine specs and test results.

POWER YOUR LIFESTYLE

STERNDRIVES

We build **Mercury MerCruiser® Sterndrive** engines and drives to power your life on the water. Our engines are engineered and built solely for marine duty. At MerCruiser, we build in the level of torque needed to lift a boat smartly on plane, and reliability you can count on year after year.



380/430 sterndrive

Because we know that sometimes you just need a big block, we build the mighty MerCruiser 8.2L. Nothing matches the pure torque of 8.2 liters of V-8 displacement in a powerband we've tuned specifically to move the heaviest boats quickly on plane. Throttle back the MerCruiser 8.2L for pleasurable low-stress cruising and outstanding fuel economy.

8.2L

6.2L

300/350 sterndrive

We designed our own V-8 6.2L to deliver the perfect balance of power, easy maintenance, superior corrosion-resistance and a quiet, pleasurable ride. Generous 6.2-liter displacement results in an outstanding power-to-weight ratio and provides a more enjoyable boating experience by letting you plane your boat quickly, handle rough seas and stay on plane at lower speeds.





200/250 sterndrive

Our engineers started from scratch to develop this powerful gem – a V-6 4.5-liter engine designed specifically for marine duty that moves a boat faster and quieter – while using less fuel – than any other engine in its class. 4.5L

JOYSTICK PILOTING FOR STERNDRIVES

Joystick Piloting for Sterndrives on dual-engine installations offers fingertip control for confident low-speed maneuvering.



DIGITAL THROTTLE & SHIFT

Available with Digital Throttle & Shift (DTS) which replaces mechanical cable controls with a silky-smooth drive-by-wire experience.



ADAPTIVE SPEED CONTROL

Adaptive Speed Control (ASC) automatically maintains a set rpm as load and conditions change in tight turns and tow-sport activities, so you'll be making fewer throttle-control adjustments.

ENGINE GUARDIAN

Our Engine Guardian System monitors multiple engine sensors and averts potential problems with timely intervention.



CORROSION PROTECTION

We battle tough marine environments with corrosion-resistant alloys, stainless steel and composites.

Our multi-step MercFusion Paint System creates an outer seal against the elements, while MerCathode® provides automatic protection against galvanic corrosion.



Available SeaCore® industrial hardcoat anodizing and freshwater (closed) cooling provide the ultimate protection in salt water.

EASIER MAINTENANCE

6.2L and 4.5L sterndrives need no 20-hour service, and feature a maintenance-free valve-train. A maintenance center on the front of the engine makes the oil dipstick, fill and filter easily identifiable and accessible.





4.5L and 6.2L sterndrives feature aft-facing throttle body, improved intake resonator and larger engine mounts that redirect engine noise away from the cockpit, while significantly reducing vibration.

It's about superior power and performance. It's about a smoother, quieter boating experience. It's about making the fun last with marine-specific parts and systems with state-of-the-art corrosion protection. All by design, not adaptation.

MERCRUISER DRIVES

Our drives are the perfect match to a powerful MerCruiser engine. From compact runabouts to heavy cruisers and go-fast speedsters, there's an ideal MerCruiser drive for each application, and the right Mercury prop to dial in responsive performance.



ALPHA ONE®

Rugged, reliable, and tested by time and countless satisfied customers, our Alpha One drive offers a sleek hydrodynamic profile that slices through the water to enhance fuel economy and control. It's rated for speeds up to 65 mph and up to 300hp in single and dual applications.



BRAVO TWO®, TWO X® AND TWO XR

Meet the king of thrust. Our Bravo Two drive family is designed to swing props up to 20 inches in diameter with a massive blade area that's ideal for pushing houseboats and lifting the heaviest cruisers on plane with ease and holding those boats on plane at lower cruising speeds to save on fuel. Rated for speeds up to 55 mph and up to 450hp in single and dual applications.



BRAVO ONE®, ONE X AND ONE XR

Bravo One drives are designed to handle the power of big block engines with a longer torpedo shape and a deeper skeg for confident control at all speeds. Dual water pick-ups keep big engines running cool at higher speeds. These drives are intended for single- and multi-engine applications that can eclipse 100 mph, with drive models rated for up to 600hp.



BRAVO THREE®, THREE X® AND THREE XR

With the added blade area of dual contrarotating propellers up to 16 inches in diameter, our Bravo Three drives really grab the water. Because the props rotate in opposite directions, they cancel prop torque for better tracking at all speeds and provide improved control around the dock, in forward gear and reverse. Rated for speeds up to 65 mph and up to 525hp in single and dual applications.

200 - 430 sterndrives

| Displacement | 4.5L | 4.5L | 6.2L | 6.2L | 8.2L MAG | 8.2L MAG H.O. |
|--------------------------------------|--|--|--|--|---|---|
| HP/kW | 200/149 | 250/186 | 300/224 | 350/261 | 380/283 | 430/321 |
| WOT RPM | 4400-4800 | 4800-5200 | 5000-5400 | 5000-5400 | 4600-5000 | 4600-5000 |
| Cylinders | V-6 | V-6 | V-8 | V-8 | V-8 | V-8 |
| Displacement | 275 cu in (4.5L) | 275 cu in (4.5L) | 377 cu in (6.2L) | 377 cu in (6.2L) | 502 cu in (8.2L) | 502 cu in (8.2L) |
| Emission Control Technology (ECT) | Yes* | Yes* | Yes* | Yes* | Yes* | Yes* |
| Fuel Injection | Multi-point Electronic Fuel Injection (MPI) | Multi-point Electronic Fuel Injection (MPI) |
| Fuel/Ethanol Tolerance | 87 Octane/up to 10% ethanol | 87 Octane/up to 10% ethanol |
| Cooling System | Thermostatically controlled raw water** | Freshwater | Freshwater |
| Engine Weight [†] | 761lbs (345kg) | 761lbs (345kg) | 882lbs (400kg) | 882lbs (400kg) | 1122lbs (509kg) | 1122lbs (509kg) |
| Engine Guardian | Yes | Yes | Yes | Yes | Yes | Yes |
| Digital Throttle & Shift (DTS) | N/A | Optional | Optional | Optional | Optional | Optional |
| Drives | Alpha | Alpha Bravo One Bravo Two Bravo Three | Bravo One Bravo Two Bravo Three | Bravo One Bravo Two Bravo Three | Bravo One X, XR Bravo Two X Bravo Three X, XR | Bravo One X, XR Bravo Two X Bravo Three X, XR |



Active Trim

Active Trim makes boating easier and more enjoyable by automatically trimming outboard and sterndrive engines. Active Trim simplifies boat operation while improving engine performance and decreasing fuel costs.

Active Trim is compatible with all current SmartCraft-capable Mercury sterndrive engines.



VesselView Mobile

VesselView Mobile allows boaters to use a mobile device (smartphone or tablet) to connect with their Mercury outboard or sterndrive engine(s). The plug-and-play module connects to your device via Bluetooth, providing quick, convenient access to your engine's data.

VesselView Mobile is compatible with all SmartCraft-capable Mercury sterndrive engines (2004 and newer).

Factory-backed

Every MerCruiser Sterndrive comes with Mercury Marine's class-leading corrosion protection. Peace of mind comes standard – thanks to Mercury's industry-exclusive three-year limited corrosion warranty. MerCruiser Sterndrives also carry a one-year factory limited factory warranty and SeaCore models carry a three-year factory limited warranty. An additional year of factory limited warranty is applied if the engine is installed by an IQ certified Boat Manufacturer.



Joystick Piloting

Mercury Joystick Piloting for sterndrives replaces stress and complexity with confidence, ease and enjoyment. Whether you're docking your boat, maneuvering in a marina or simply needing to hold your position despite wind and current, you will experience complete control delivered by Joystick Piloting.

Available on all dual-engine MerCruiser Sterndrive installations 250hp and up.







375/425 inboard

The pure, brawny muscle of our big-block V-8 inboards inspires confidence. We deliver 8.2 liters of smooth, quiet, efficient power from an engine that's been tuned specifically for inboard duty. At cruising speed these big V-8 engines barely break a sweat.

8.2L



6.2I

300/350 inboard

Mercury engineers optimized every design element of the MerCruiser 6.2L engine for marine duty. It offers extra displacement for more of the torque you need to lift an inboard boat on plane and keep it there. We designed an entire system of features to suppress engine sound and vibration. All you'll feel is power. Boating has never been so enjoyable.





DIGITAL THROTTLE & SHIFT

MerCruiser Inboards come standard with Digital Throttle & Shift (DTS) which replaces mechanical cable controls with a silky-smooth driveby-wire experience.



JOYSTICK PILOTING FOR INBOARDS

Combine our Digital Throttle & Shift (DTS) controls with available Joystick Piloting for Inboards and enjoy the ultimate in low-speed control and maneuverability at the touch of a finger. Joystick Piloting for Inboards comes standard with a thruster-only feature for large dual engine boats, allowing the driver to easily adjust heading by bumping the joystick. This is the only inboard joystick system for boats with single engines.



ADAPTIVE SPEED CONTROL

Adaptive Speed Control (ASC) automatically maintains a set rpm as load and conditions change in tight turns and tow-sport activities, so you'll be making fewer throttle-control adjustments.

CORROSION PROTECTION

Our comprehensive anti-corrosion package is backed by a four-year limited warranty. Freshwater (closed) cooling is standard on the MerCruiser 6.2L inboard, and it replaces raw water with long-life five-year coolant.



Available SeaCore® industrial hardcoat anodizing and freshwater (closed) cooling provide the ultimate protection in salt water.

ENGINE GUARDIAN

Our Engine Guardian System monitors multiple engine sensors and averts potential problems with timely intervention.







300 - 425 inboards

320/370 tow sport inboards

| Displacement | 6.2L | 6.2L | 8.2L Horizon | 8.2L H.O. | 6.2L | 6.2L |
|--------------------------------------|--|--|--|--|--|--|
| HP/kW | 300/224 | 350/261 | 375/280 | 425/317 | 320/239 | 370/276 |
| WOT RPM | 5000-5400 | 5000-5400 | 4200-4600 | 4400-4800 | 5000-5400 | 5000-5400 |
| Cylinders | V-8 | V-8 | V-8 | V-8 | V-8 | V-8 |
| Displacement | 377 cu in (6.2L) | 377 cu in (6.2L) | 502 cu in (8.2L) | 502 cu in (8.2L) | 377 cu in (6.2L) | 377 cu in (6.2L) |
| Emission Control Technology (ECT) | Yes* | Yes* | Yes* | Yes* | Yes* | Yes* |
| Fuel Injection | Multi-point Electronic Fuel Injection (MPI) |
| Fuel/Ethanol Tolerance | 87 Octane up to10% ethanol |
| Cooling System | Thermostatically controlled Freshwater | Thermostatically controlled Freshwater | Thermostatically controlled Freshwater | Thermostatically controlled Freshwater | Thermostatically controlled raw water** | Thermostatically controlled raw water** |
| Engine Weight [†] | 947lbs (430kg) | 947lbs (430kg) | 1122lbs (509kg) | 1122lbs (509kg) | 862lbs (391kg) | 862lbs (391kg) |
| Engine Guardian | Yes | Yes | Yes | Yes | Yes | Yes |
| Digital Throttle & Shift (DTS) | Standard | Standard | Standard | Standard | Optional | Optional |

Factory-backed



Every MerCruiser Inboard comes with Mercury Marine's classleading corrosion protection. Peace of mind comes standard – thanks to Mercury's industry-exclusive three-year limited corrosion warranty. MerCruiser Inboards also carry a three-year factory limited warranty and Tow Sport Inboards carry a two-year limited warranty. An additional year of factory limited warranty is applied if the engine is installed by an IQ certified Boat Manufacturer.

Joystick Piloting

Mercury Joystick Piloting for inboards replaces stress and complexity with confidence, ease and enjoyment. Whether you're docking your boat, maneuvering in a marina or simply needing to hold your position despite wind and current, you will experience complete control delivered by Joystick Piloting.

Available on all MerCruiser Inboard engines.

Optional on MerCruiser Tow Sport Inboard engines.





6/7

4.2L



480 / 500 / 550 DIESEL

Experience a new level of responsive power for sport yachts that boasts 20 percent quicker acceleration and faster top speed than the competition. This L6 common rail engine utilizes design features and materials specific to marine applications; is compatible with all Mercury controls, VesselView displays and SmartCraft electronics; and is backed by the global Mercury service network.



335 / 370 DIESEL

The common-rail Turbo Direct Injection (TDI) technology used by Mercury is a combustion system that turns every drop of fuel into big power and torque for superior running efficiency and class-leading fuel economy. In fact, 50 percent better fuel economy than comparable power gas engines. More miles between fuel docks. More quality time on the water.

3.0_L

2.0L



230 / 260 DIESEL

The outstanding power density of our V-6 diesel engine is the product of an ultra-lightweight design paired with power-boosting technology. The result is strong hole-shot performance from a compact engine package that can fit in virtually any installation. The V-6 diesel is fully SmartCraft compatible and can be rigged with Digital Throttle & Shift (DTS) controls and Mercury Joystick Piloting for Sterndrives (JPS) docking and maneuvering control.



150 / 170 DIESEL

Reliable, compact and robust, our 2.0L diesel engine is an L4 design that offers excellent power density and leading technology. Common rail fuel injection and solenoid fuel injectors deliver precise fuel control for clean operation and efficiency that will extend your range and decrease costs. This engine is compatible with Mercury Diesel Alpha and Bravo series drives.

DIGITAL THROTTLE & SHIFT

Full Mercury SmartCraft compatibility provides access to dozens of engine, boat and navigation options, plus available Digital Throttle & Shift (DTS) control systems.





JOYSTICK PILOTING


Pair available Mercury Digital Throttle and Shift (DTS) controls with Mercury Joystick Piloting for Inboards (JPI) in single-engine and twin-engine applications, Joystick Piloting for Sterndrives (JPS) or Zeus Pod Drives. With a simple push or twist of the joystick, you can move the boat from side to side, diagonally or even spin on a single axis.

RESISTING CORROSION

Our diesel engines provide state-of-the-art anticorrosion features, including a thermostatically controlled closed water-cooled system. Watercooled engine oil, gear oil and steering fluid decrease engine-room temperatures to extend the life of the engine.



You can count on the optional SeaCore® system for the ultimate in salt water protection in the harshest conditions.



ZEUS POD DRIVES

Our Zeus® pod drives (for 500hp and 550hp) offer unmatched performance, safety and vessel systems control. Outstanding fuel efficiency and performance are delivered from horizontal thrust angles, contra-rotating propellers and a superior hydrodynamic shape. Independent steering provides greater control at high and low speeds, while smooth and quiet operation enhances the boating experience for everyone aboard.

DIESEL DRIVES

For every high-performing Mercury Diesel engine, there's an equally high-performing drive. Working together to give you better performance. Whatever your boating style. Each drive is designed, built, and tested to deliver best-in-class reliability.



ALPHA ONE®

Available for single and twin engine applications, the Alpha One's efficient hydrodynamic profile produces very little drag, which means better boat performance and fuel economy.

Designed for boats capable of up to 150hp.



BRAVO TWO X® DIESEL AND TWO XR DIESEL

Meet the king of thrust. Our Bravo Two drive family is designed to swing props up to 20 inches in diameter with a massive blade area that's ideal for pushing houseboats and lifting the heaviest cruisers on plane with ease and holding those boats on plane at lower cruising speeds to save on fuel. Rated for speeds up to 55 mph and up to 370hp in single and dual applications.



BRAVO ONE X® DIESEL AND ONE XR DIESEL

Bravo One drives are designed to handle the power of big block engines with a longer torpedo shape and a deeper skeg for confident control at all speeds. Dual water pick-ups keep big engines running cool at higher speeds. These drives are intended for single- and multi-engine applications that can eclipse 55 mph, with drive models rated for up to 370hp.



BRAVO THREE X® DIESEL AND THREE XR DIESEL

With the added blade area of dual contrarotating propellers up to 16 inches in diameter, our Bravo Three drives really grab the water. Because the props rotate in opposite directions, they cancel prop torque for better tracking at all speeds and provide improved control around the dock, in forward gear and reverse. Rated for speeds up to 65 mph and up to 370hp in single and dual applications.

115 - 370 tier 3 diesel

| Displacement | 2.0L | 2.0L | 2.0L | 2.0L | 3.0L | 3.0L | 4.2L | 4.2L | 6.7L | 6.7L | 6.7L | | |
|-------------------------------|-------------------------------|---------|------------------------|----------------------------------|--------------------|---|-------------------------|------------------------------|-------------------------------------|----------|-------------|--|--|
| Horsepower | 115 | 130 | 150 | 170 | 230 | 260 | 335 | 370 | 480 | 500 | 550 | | |
| Rated RPM | | 40 | 00 | | 4000 | | 4200 | | 3200 | | | | |
| Cylinders | | Inlir | ne-4 | | V- | V-6 | | V-8 | | Inline-6 | | | |
| Dry Weight* | 551lbs (250kg) 582lbs (264kg) | | | | 675lbs | (306kg) | 836lbs | (379kg) | 1,642lbs (745kg) | | | | |
| LxWxH | | 32 x 28 | 3 x 29in | | 37 x 33 x 34in | | 41 x 33 x 33in | | 43 x 35 x 34in | | | | |
| Aspiration | Turboc | harged | Turbocha | rged (VGT) | Turbocharged (VGT) | | Twin Turbocharged (VGT) | | Turbocharged | | | | |
| Fuel Injection | | | ressure Rail (HPCR) | | | High Pressure High Pressure Common Rail (HPCR) Common Rail (HPCR) | | | High Pressure Common Rail (HPCR) | | | | |
| Cooling System | | Fresh | water | | Fresh | water | Fresh | nwater | Freshwater | | | | |
| Digital Throttle& Shift (DTS) | | Opti | onal | | Opti | onal | Optional | | Standard | | | | |
| Drives | Shaft drive | Alpha | Bravo Bravo | oha One X Two X Three X | Bravo Tv | ne X, XR wo X, XR ree X, XR | Bravo | One XR Two XR Three XR | Shaft drive Zeus Pod or shaft dr | | shaft drive | | |



Factory-backed

Every Mercury Diesel comes with class-leading corrosion protection and an industry-exclusive three-year limited corrosion warranty. Mercury Diesel engines also carry a two-year factory limited warranty and Diesel Tow Sport Inboards carry a three-year limited warranty. 6.7L Tier 3 Diesel engines carry a three-year limited warranty plus two years on major components. An additional year of factory limited warranty is applied if the engine is installed by an IQ certified Boat Manufacturer. Certified installations of Diesel Inboard Shaft Tow Sport applications receive two additional years of Standard Limited Warranty.

115 – 350 tier 2 diesel

| Displacement | 2.0L | | 2.8L | 4.2L | | | 6.7L | | | | | | | | |
|--------------------------------|-------------------------------------|-------|--------------------------------|-------------------------------------|---|-------|---|--------------------------------------|-----------------|---------|-----------|-----|----------|-----|-------|
| Horsepower | 115 | 130 | 150 | 170 | 220 | 270 | 320 | 350 | 135 | 150 | 200 | 180 | 230 | 260 | 280 |
| Rated RPM | 3000 | 4000 | | 3800 | 3800 | | | 3200 | | | | | | | |
| Cylinders | Inline-4 | | Inline-4 | Inline-6 | | | Inline-6 | | | | | | | | |
| Dry Weight* | 551lbs (250kg) 582lbs (264kg) | | 794lbs (360kg) | 1014lbs (460kg) | | | 1169lbs (530kg) 1334lbs (605kg) 1334lbs | | | | (605kg) | | | | |
| LxWxH | 32 x 28 x 29in 32 x 28 x 30in | | 34 x 31 x 32in | 43 x 31 x 32in | | | 43 x 28 x 36in 43 x 32 x 32in 43 x | | | 43 x 32 | 32 x 31in | | | | |
| Aspiration | Turbocharged | | | Turbocharged | Turbocharged | | | Turbocharged | | | | | | | |
| Fuel Injection | High Pressure Common Rail (HPCR) | | | High Pressure Common Rail (HPCR) | High Pressure Common Rail (HPCR) | | | Mechanical Fuel Injection | | | | | | | |
| Cooling System | Freshwater | | Freshwater | Freshwater | | | Freshwater | | | | | | | | |
| Digital Throttle & Shift (DTS) | Optional | | | Optional | Optional | | | N/A | | | | | | | |
| Drives | Shaft drive | Alpha | Alp Bravo Bravo Bravo | One X | Bravo One X Bravo Two X Bravo Three X | Bravo | Ine X, XR Two X Iree X, XR | Bravo One XR Bravo Three X, XR | Bravo Two X, XR | | | ? | Shaft dı | | drive |



Engines

Mercury engines have set and reset the standards for reliable, trouble-free performance; superior power and torque; low emissions; and low fuel consumption. And nobody has given boaters more ways to propel their boats, activities, and pursuits reliably, comfortably, and efficiently across the water.

Propellers

Propeller selection can impact virtually every aspect of your boat's performance, and Mercury has a solution for every propeller challenge. It's no wonder you see Mercury propellers on boats of all engine brands.

Controls

Mercury controls are engineered, built and tested for technical precision and easy operation. Choose from side mounts, flush panel mounts and console mounts with combined speed and trim functions, engine warm up, and more.

Digital Throttle & Shift

Digital Throttle and Shift (DTS) provides precise handling, seamlessly connects with compatible displays, and delivers instant response and total control with no hesitation.

Active Trim

Mercury Active Trim for outboards and sterndrives automatically trims your boat, which simplifies operation while improving performance and decreasing fuel costs. With Active Trim, new boaters and experienced captains can achieve perfect trim without constantly monitoring and adjusting the trim control.

Joystick Piloting

Whether you're docking your boat, maneuvering in a marina or simply needing to hold your position despite wind and current, you will experience complete control delivered by Joystick Piloting. With intuitive fingertip command you can effortlessly make your boat do exactly what you want it to do.

Learn more about Mercury Joystick Piloting on pages 82 and 83.

Displays

Stay in the know by having the status of your propulsion system available at a glance, be notified visually and audibly should an issue arise, and trust that you have the most integrated solution available providing advanced control features such as Troll Control, SmartTow Launch Control and Active Trim.

VesselView

Mercury VesselView can display engine and boat performance information, genset function, sounder and much more. It has access to more information and data on boat and engine functions than any other system in the boating industry. You can monitor up to four engines simultaneously on an intuitive "at a glance" LCD Screen.

VesselView Mobile

VesselView Mobile lets you use your mobile device (smartphone or tablet, Android or iPhone) to connect via Bluetooth with your Mercury engine to display VesselView data on the device. The plug-and-play engine module provides quick, convenient access to your engine's data.

VesselView Link

Offered in single-engine or multi-engine versions (two to four engines), VesselView Link connects all features offered by SmartCraft to compatible Lowrance and Simrad displays, placing the complete VesselView information suite and control capability on your main helm display.

Learn more about Mercury propulsion systems at **MercuryMarine.com**





JOYSTICK PILOTING

TAKE CONTROL


Mercury Joystick Piloting for outboards, sterndrives, inboards and pods replaces stress and complexity with confidence, ease and enjoyment. Whether you're docking your boat, maneuvering in a marina or simply needing to hold your position despite wind and current, you will experience complete control delivered by Joystick Piloting. With intuitive fingertip command you can effortlessly make your boat do exactly what you want it to do.

360° CONTROL

Move your boat in any direction Perform combined commands, such as simultaneously rotating and with confidence in tight spaces despite wind and current.









ROUTE

Route automatically navigates to active waypoints. Just program the route and the system does the rest.

SKYHOOK® DIGITAL ANCHOR

Skyhook digital anchor locks in a boat's position using GPS, then works with the engines and drives to maintain position and heading with the push of a button – regardless of wind or current.





HEADING

Auto heading uses an integrated digital compass to automatically maintain your boat's heading to keep you on your desired path.

JOYSTICK PILOTING FOR OUTBOARDS

Joystick Piloting for Outboards – designed for dual, triple and quad Verado-powered vessels and personalized for each boat model – was the industry's first joystick system for outboards, and it remains the best-selling marine joystick system.

Available on 250, 300 and 350hp Verado and 300hp SeaPro AMS outboards.







X7® ALLOY

Our proprietary X7 stainless-steel alloy is 30 percent stronger and four times more durable than conventional stainless, which allows us to design revolutionary props that otherwise would be impossible.



MERCALLOY®

Our patented Mercalloy aluminum is designed specifically for the diecast process and helps us produce the highest quality props, free of porosity for increased strength.



Use the exclusive PVS® system to custom tune the venting of your propeller, allowing your boat to achieve optimal acceleration.

FLO-TORQ® HUB SYSTEM

The Flo-Torq II system provides a cushion between the engine and prop to protect the drivetrain from most impacts, and it offers unmatched corrosion protection. Flo-Torq SSR technology is available for outboard owners seeking the smoothest-shifting hub system on the market.





PROPELLERS

Stronger materials, more innovative designs, and unmatched engineering expertise keep Mercury ahead of the competition. And it will keep you ahead of the pack. From eye-watering speeds for tournament pros to unmatched pulling power for tow sports, Mercury propellers deliver.



ENERTIA®

- X7 Alloy and PVS
- Improves top speed and acceleration of outboards and sterndrives
- Our top-performing prop for highhorsepower pontoons
- For 90hp and above Command Thrust outboards, and MerCrusier Alpha One and Bravo One



FURY®

- X7 Alloy and PVS
- Revolutionary performance for tournament bass boats
- Reduced diameter and large blade area boosts speed and acceleration
- Top performance for 250hp outboards on bass, bay and flats boats



ENERTIA ECO

- X7 Alloy and PVS
- Up to 10 percent better fuel economy at cruising speed
- No-compromise performance
- Best for 250hp outboards on heavy offshore boats



FURY 4®

- X7 Alloy and PVS
- Four-Blade design
- Designed to lift heavy 20-to-22foot bass and walleye boats
- Perfect for 250hp outboards with a full tournament load

REVOLUTION 4®

- Stainless steel and PVS
- Aggressive four-blade design
- Outstanding hole shot and superior rough-water holding
- Ideal for 250hp outboards on center consoles




SPITFIRE®

- Mercalloy
- Aggressive four-blade design that's also affordable
- Combines three-blade speed with four-blade hole shot
- Best matched to 25hp to 150hp outboards and MerCruiser Alpha One



SPITFIRE X7

- X7 Alloy and PVS
- High-performance all-purpose propeller
- Strong acceleration, top speed and holding
- Designed for FourStroke 75hp to 115hp outboards



BRAVO THREE®

- Stainless-steel
- Four-blade front and threeblade rear contra-rotating design
- Improves speed, acceleration, holding and economy
- Exclusively for MerCruiser Bravo III





MERCURY PRECISION PARTS®

THE ORIGINAL SOURCE OF QUALITY

Craftsmanship sets the tone for your vessel, and even the smallest details can be critical. That's why Mercury is committed to providing precision parts made specifically for all Mercury engines. Mercury parts and accessories are designed and built to deliver original factory fit and performance to keep your Mercury engine running like new and your boating experience trouble-free.





MERCURY MAINTENANCE PRODUCTS


Mercury Maintenance Products help you maximize enjoyment and avoid frustration. You should never have to guess which products will keep your engine running at peak performance. You can find Mercury maintenance items such as one-stop maintenance kits, oil-change kits, filters and all other maintenance parts at your local Mercury dealer.





MERCURY PRECISION LUBRICANTS®

When it comes to protecting your engine, trust the people who made it. Mercury oils and lubricants are specially formulated and tested in-house to help your engine deliver optimal performance for a better boating experience. Mercury oils and lubricants meet the demands of all marine environments, and they meet the high standards Mercury Marine sets for all its products.







Tel: 1-239-228-6713

www.amzimmarineservices.com



MercuryMarine.com

MAY 2018 90-8M0107294

© 2018 Mercury Marine. All Right Reserved. Reproduction in whole or in part without permission is prohibited. Alpha One, Bravo One, Bravo Two, Bravo Two X, Bravo Three, Bravo Three X, Circle M Logo, Enertia, Flo-torq, Fury, Go Boldly, Harris, Lowe, Lund, Mercalloy, Mercury, MerCruiser, Mercury Marine, Mercury Precision Lubricants, Mercury Precision Parts, Mercury Propellers, OptiMax, Princecraft, Pro XS, PVS, Revolution 4, SeaCore, Skyhook, SmartCraft, Spitfire, SportJet, Verado, VesselView, X7 are registered trademark of Brunswick Corporation. SeaPro and VesselView Mobile are trademarks of Brunswick Corporation. Mako and Nitro are registered trademarks of Tracker Marine, Yellowfin is a registered trademark of Yellowfin Yachts, Inc.

Product information in this brochure is accurate as of May 18, 2018. For the latest content, please visit MercuryMarine.com